



DIESEL FUEL ADDITIVE

ALL SEASON DIESEL BOOST

INJECTOR CLEANER



DESCRIPTION:

PEAK ALL SEASON DIESEL BOOST is a multifunctional high performance detergent additive that uses advanced technology to clean traditional and metal carboxylate deposits in all diesel applications. This advanced formula designed for today's High Pressure Common Rail (HPCR) fuel injection system, has been extensively evaluated within OEM on-road vehicle fleets and heavy diesel mining applications.

PEAK ALL SEASON DIESEL BOOST is designed for year round use to ensure reliable fuel system performance in all diesel applications and is compatible with all fuel system components. This technology is effective in all diesel fuels including biodiesel blends and is also an excellent tank maintenance additive for bulk fuel storage tanks.

BENEFITS:

- Effective on both traditional and metal carboxylate deposits created in HPCR systems
- Cleans and maintains injector cleanliness by preventing new deposits from forming
- Restores injector performance, lost horsepower and optimizes fuel economy up to 8%
- Provides diesel fuel stability, lubricity, corrosion protection, and water dispersancy
- Prevents formation of soot and sludge caused by thermal stresses
- Extends fuel filter, injector, lube oil, and fuel pump life
- Reduces exhaust emissions, thereby reducing EGR manual regenerations
- Reduces cost of maintenance and downtime
- Contains less than 15 ppm sulfur and burns ash free

TREATMENT RATES

Available Sizes

Treat Rate

2.5 Gal
Drum
Tote

1:1500 gallon

Treat rates may vary due to regional fuel characteristics. Please contact your PEAK Commercial & Industrial representative for recommendations.

PROPERTIES:

TYPICAL VALUES

Physical State	Liquid
Color	Colorless Amber
Order	Petroleum-Like Odor
Flash Point	72 °C (162 °F)
Specific Gravity	0.9 @ 15.6 °C (60.1 °F)
Density	7.54 lbs/gal @ 15.6 °C (60.1 °F)
Solubility	Water: Insoluble
Viscosity, kinematic	2.9 mm ² /s @ 40 °C (104 °F)

SHIPPING INFO:

Description	2.5 Gal	55 Drum Gal	275 Gal Tote
Part#	PCIASDB2.5	PCIASDB01	PCIASDB275
UPC Code	0-74804-05943-4	0-74804-059444-1	0-74804-05945-8
Case UPC	0-74804-15943-1	-	-
Case SCC-14 Code	1-00-74804-05943-1	1-00-74804-05944-8	1-00-74804-05945-5
Case Weight/Cube	36 lbs.	410 lbs. (per drum)	2070 lbs. (per tote)
Pack/Unit Case	2	-	-
Unit Dimensions	6.67"l x 9.12"w x 14.38"h	23.5"dia x 34.5"h	48"l x 40"w x 46"h
Case Dimensions	10.25"l x 14.5"w x 16"h	-	-
Units/Cases per Pallet	36 (cases)	4 (drums)	1 (tote)
Units per Truck	1,584	80 drums	14 totes
Truckload Weight	22 pallets per truck - 29,392 Lbs	20 pallet/truck - 33,600 lbs.	28,980 lbs
Pallet Size	44"l x 44"w x 51"h	44"l x 44"w x 39"h	48"l x 40"w x 46"h
Pallet Weight	1336 lbs.	1680 lbs.	2070 lbs.
Cases/Rows High	12/3	-	-

(*) Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Safety Data Sheet available upon request.

Distributed by Old World Industries, LLC Northbrook, IL 60062
800.323.5440



peakhd.com

CHEMISTRY THAT DRIVES COMMERCE™
©2018 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.