

The 3.62" DEF filter unit holds a standard sized filter. The strong plexiglass filter housing allows for a visual filter check. Ensuring the DEF you pump is clear of all particles.



- ISO 22241 compatible
- Helps to ensure product purity
- Eliminates most contamination/particulation
- "G" Style fittings for ease of installation
- Easily change filter
- Acrylic housing for enhanced inspection of fluid quality



TECHNICAL DATA

CASING:

Casing Inlet, top:	G 1" female
Outlet, side:	G 1" female
Material, housing, upper part:	polyamide
Material, housing, lower part:	plexiglasS
Seal material:	Viton® FKM
Operating temperature area (°C):	-5 / +60
Operating pressure max. (bar):	2.5
Media:	DEF

FILTERING CANDLE:

Material:	polypropylene
Outside diameter (inch):	2.48
Inner diameter (inch):	1.10
Length (inch):	3.62
Separation efficiency (µm):	5
Filter surface (cm²):	190

Dimensions LxWxH (inch):	7.48 x 5.16 x 4.17
Weight (lb):	0.93

PACKAGING

Packaging:	white carton
Dimensions LxWxH (inch):	5.83 x 5.24 x 5
Weight including package (lb):	1.54
Packaging unit:	1.0

DEFTBFL96

UPC: 0-74804-06503-9

SCC 14 Bar Code: 1-00-74804-06503-6

SPECIFICATION

- 4-layer filter candle 3.62 inch
- Filter unit includes filter
- Seal kit for filter housing and fittings
- Visual filter check
- Tool-free filter replacement
- Easy to clean filter can also be operated without filter cartridge
- Double sealing system, axial + radial, no crystal formation due to leaking DEF
- Dual seal system for all fittings and connecting parts
- Standard filter cartridge size

