

The Drum Hand Pump System is specifically designed, engineered, and manufactured to securely attach and efficiently pump diesel exhaust fluid from drums.

- Drum Hand Pump System includes expandable downtube, drum adapter and poly manual nozzle with lock pin feature
- Drum adapter allows precise connection of pump on the drum
- Efficient DEF delivery rate, per manual pump stroke

## TECHNICAL DATA

**Delivery Rate (gal./stroke):** 0.13

**Delivery Rate (gpm):** approx. 13.21

**Pumping Media:** DEF, non-aggressive liquids such as detergents, soaps, anti-freeze, windscreen wash, hydraulic oils, herbicides and pesticides container, for 12/52/58 gal.

### USAGE:

Length of suction tube (inch): 39.37  
Barrel screw coupling: G 2" male

### MATERIALS OF PARTS IN CONTACT WITH LIQUID:

Pump Body: PP  
Seals: FKM  
Suction pipe: PP

**Dimensions L x W x H (inch):** 10.24 x 4.92 x 52.36  
**Weight (lb):** 1.32

## PACKAGING

**Packaging:** white carton  
**Dimensions LxWxH (mm)/(inch):** 14.37 x 13.78 x 12.40  
**Weight including package (kg)/(lb):** 5.42  
**Packaging unit:** 1



**DEFDPHP (Manual Poly Nozzle)**

UPC: 0-74804-06473-5  
CASE SCC 14: 1-00-74804-06473-2

## SPECIFICATION

- Discharge hose 19.7 ft
- Poly nozzle for DEF with swivel
- Drum adapter fitting

## SPECIAL NOTES

In the case of crystal formation, clean the pump with warm water until all crystals are dissolved

