

The 396 gallon PNP offers everything needed to ensure your operation has the capability to store and pump the DEF you need in this compact and quality station.

- DEF PNP includes tank level indicator, 120V diaphragm pump, in-line digital meter, leakage alarm, 20 ft discharge hose and stainless steel automatic shut-off nozzle
- Pre-wired and ready for operation
- Heated Tank Option Available



DEF396

UPC: 0-74804-06507-7

SCC 14 Bar Code: 1-00-74804-06507-4

TECHNICAL DATA

Tank:

Tank volume (gal.):	396
Material tank:	PE-LLD Lupolen 4021 K RM
Color outer tank:	blue, RAL 5015
Color inner tank:	white
Color of the door:	blue, RAL 5015
Removable lid of the outer tank, LxW (inch):	66.14 x 36.42
Diameter of the manhole in the inner tank (inch):	22.24
Dimensions of the access door, WxH (inch):	28.74 x 60.24
Fixing points:	using inserts

PUMP:

Pump design:	diaphragm, self-priming
Delivery rate under free discharge up to (gpm):	9.2
Discharge pressure up to (psi):	26.4
Pumping media:	DEF

MOTOR DATA:

Voltage (V):	120
Frequency (Hz):	60
Power consumption (A):	2.8
Thermal protection:	self-resetting
Duty cycle:	continuous operation
Protection class:	IP 54

Dimensions LxWxH (mm)/(inch): 67.1 x 48.84 x 94.48

Weight (kg)/(lb): 793.66

SPECIFICATION

- Double walled tank
- Wall thickness up to 0.28 inch
- Diffusion and UV-resistant
- Filling valve G2"
- 2" Dixon Dry-Break
- Ventilation valve
- Pneumatic level indicator, in %
- Optical and visual leakage alarm
- Stainless steel foot valve with filter
- Lockable door using 2 padlocks
- Diaphragm pump with integrated bypass, mounted on a stainless steel plate
- On/Off switch
- In-line digital meter
- Discharge hose, 20 ft
- Stainless steel nozzle with rotary swivel

SPECIAL NOTES

- Heated Tank Option Available - Item # DEF396H

