

The manual shut-off nozzle is a very economical nozzle for transferring DEF. This lightweight nozzle has a poly body with a stainless steel spout.

- Compatible with all BlueDEF pumps and systems.
- Lock pin feature



DEF-MN

UPC: 0-74804-06500-8

SCC 14 Bar Code: 1-00-74804-06500-5

TECHNICAL DATA

| | |
|---------------------------------------|----------------------------------|
| Connection: | G 1" male with hose liner, NW 19 |
| Flow capacity max. (l/min): | 80 |
| Outside diameter discharge tube (mm): | 18 |
| Hose connection Swivel: | DN 19 |
| Housing material: | plastic |
| Material discharge spout: | stainless steel- |
| Switch-off: | manually |
| Working pressure (bar): | 0.5 - 4 |
| Operating pressure max. (bar): | 4 |
| Dimensions LxWxH (inch): | 12.99 x 6.69 x 1.97 |
| Weight (lb): | 1.17 |

PACKAGING

| | |
|---------------------------------------|---------------------|
| Packaging: | white carton |
| Dimensions LxWxH (inch): | 15.75 x 6.69 x 2.36 |
| Weight including package (lb): | 1.17 |
| Packaging unit: | 1.0 |

SPECIFICATION

- Automatic nozzle for DEF with swivel

SPECIAL NOTES

- In the case of the formation of crystals: To dissolve the crystals, bring the DEF nozzle in the compressed [open] position and put it in hot water for half an hour (max. 50°C)

