

The Mini Bulk system showcases UV resistant, stainless steel outer panels and roof that are insulated for hot to cold climates. Every part and component are certified ISO 22241 DEF compatible to ensure you never have to worry about contaminants compromising the chemistry. This system is pre-wired for easy installation and can hold and expand in 500 gallon increments up to 2,000 gallons. Features an automated fill-port valve (to prevent overfilling), dry-break adapter fill port, high-level indicator and weather-tight control panel mounted on front wall. The Mini Bulk is designed to fit on a fuel island.



Includes lockable fill port door and a ½ HP submersible DEF pump. Also includes forklift pockets for quick relocation.

TECHNICAL DATA

500 GALLON (1 TANK)	
Height	107"
Width	36"
Length	48" + 8" control box
Weight (empty)	~1,035 lbs
Weight (full)	~5,600 lbs
Flow Rate	~15 gpm max**
System Pressure	60 psi (36 operating)
Standard Voltage	120V 60 Hz (240V optional)
Maximum Pump Amperage	9A (20A circuit)
Maximum Heater Amperage	12A (20A circuit)
ISO 22241-3 & 22241-1 Standards	Complies
Additional Standards Compliance	Complies to NFPA 30, 30A, 70 if installed properly <i>(refer to local codes)</i>

1000 GALLON (2 TANKS)	
Height	107"
Width	36"
Length	96" + 8" control box
Weight (empty)	~1,900 lbs
Weight (full)	~11,000 lbs
Flow Rate	15 gpm max**
System Pressure	60 psi (36 operating)
Standard Voltage	120, 60 Hz (240V optional)
Maximum Pump Amperage	25A (30A circuit)
Maximum Heater Amperage	23A (30A circuit)
ISO 22241-3 & 22241-1 Standards	Complies
Additional Standards Compliance	

FEATURES

- Unit fits on all standard width fuel islands
- Modular design allows the equipment to grow with increasing DEF demand
- Polished stainless steel outer panels and roof
- High density polyethylene tank with no bottom or side-wall penetrations
- Keeps fluid safe from environmental hazards
- Easily relocatable
- Integrates with any brand commercial, fleet or retail dispenser
- 120V design standard with a 1/2 HP submersible DEF pump
- Pre-wired electrical components
- Installation anchor kit
- Lockable fill-port
- High level indicator with overfill protection valve
- Automatic low lever shut down protection

OPTIONS/ADD ONS

Level display	Advertising rails
Heat package	3/4 HP or 1 HP submersible pump
Dispensing Cabinet with filter	
Remote inventory management	

