



PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Motor Oil

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
4065 Commercial Ave.
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300; (703) 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

Signal word (GHS-US) : None
Hazard statements (GHS-US) : None
Precautionary statements (GHS-US) : P273 - Avoid release to the environment
P501 - Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

2.3. Other hazards

Other hazards not contributing to the classification : The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % by wt | GHS-US classification |
|--|---------------------|---------|--|
| distillates (petroleum), hydrotreated heavy paraffinic | (CAS No) 64742-54-7 | 40 - 70 | Acute Tox. 3 (Inhalation:vapor), H331 Acute Tox. 4 (Inhalation:vapor), H332 |

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------------|---|
| First-aid measures after skin contact | : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. |
| First-aid measures after ingestion | : Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|--------------------------------------|---|
| Symptoms/injuries after inhalation | : ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation. |
| Symptoms/injuries after skin contact | : Contact during a long period may cause slight irritation. |
| Symptoms/injuries after eye contact | : Direct contact with the eyes is likely to be irritating. |
| Symptoms/injuries after ingestion | : Ingestion is likely to be harmful or have adverse effects. |

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. Will float and can be reignited on water surface. |

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|--|
| Fire hazard | : Not flammable. Promotes combustion. |
| Explosion hazard | : Not applicable. |
| Reactivity | : No dangerous reactions known under normal conditions of use. |

5.3. Advice for firefighters

| | |
|--|---|
| Firefighting instructions | : Cool tanks/drums with water spray/remove them into safety. Fight fire with normal precautions from a reasonable distance. Under fire conditions, hazardous fumes will be present. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. |
| Special protective equipment for fire fighters | : Protective fire fighting clothing (includes fire-fighting helmet, coat, pants, boots and gloves). Wear positive pressure self-contained breathing apparatus (SCBA). |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|--|
| General measures | : Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray. |
|------------------|--|

6.1.1. For non-emergency personnel

| | |
|----------------------|--|
| Protective equipment | : Use appropriate personal protection equipment (PPE). |
| Emergency procedures | : Evacuate unnecessary personnel. |

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Equip cleanup crew with proper protection. |
| Emergency procedures | : Stop leak if safe to do so. Ventilate area. |

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|---|
| For containment | : Contain leaking substance. Plug the leak, cut off the supply. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. |
| Methods for cleaning up | : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. |

6.4. Reference to other sections

No additional information available

PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Store in a dry place. Store in a well-ventilated place. Keep cool. Keep container closed when not in use. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not store near food, foodstuffs, drugs or potable water supplies.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5 | | |
|---|-------------------------------------|--|
| ACGIH | ACGIH TWA (mg/m ³) | 5.00 mg/m ³ Chemical name: Oil mist, mineral |
| ACGIH | ACGIH STEL (mg/m ³) | 10.00 mg/m ³ Chemical name: Oil mist, mineral |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ Chemical name: Oil mist, mineral |
| OSHA | Remark (OSHA) | Skin notation |

| distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | | |
|---|--------------------------------|--|
| ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ (Mineral oil, pure, highly and severely refined; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction) |
| OSHA | Not applicable | |

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Personal protective equipment : Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



- Hand protection : Wear suitable gloves resistant to chemical penetration.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : brown
- Odor : petroleum-like odor
- Odor threshold : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : 206 °C (402 °F) [Method used: Cleveland Open Cup]
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available

PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------|----------------------------|
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Specific Gravity | : 0.85 |
| Density | : 0.85 kg/l (7.09 lbs/gal) |
| Solubility | : Water: Negligible |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : 48.31 cP |
| Explosive properties | : Not applicable. |
| Oxidizing properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

| | |
|-------------|----------|
| VOC content | : 0.00 % |
|-------------|----------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------|------------------|
| Acute toxicity | : Not classified |
|----------------|------------------|

| distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|--|---|
| LD50 oral rat | > 5,000.00 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental value) |
| LD50 dermal rabbit | > 5,000.00 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402) |
| LC50 inhalation rat (mg/l) | > 5.53 mg/l/4h (Rat; Experimental value) |
| ATE US (vapors) | 3.00 mg/l/4h |

| | |
|---------------------------|------------------|
| Skin corrosion/irritation | : Not classified |
|---------------------------|------------------|

| | |
|-----------------------------------|------------------|
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |

| | |
|--|------------------|
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : Not classified |

| | |
|--|------------------|
| Specific target organ toxicity (repeated exposure) | : Not classified |
|--|------------------|

| | |
|-------------------|------------------|
| Aspiration hazard | : Not classified |
|-------------------|------------------|

Symptoms/injuries after inhalation : ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.

Symptoms/injuries after skin contact : Contact during a long period may cause slight irritation.

PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion : Ingestion is likely to be harmful or have adverse effects.

SECTION 12: Ecological information

12.1. Toxicity

| distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|---|
| LC50 fish 1 | > 100.00 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value) |
| Threshold limit algae 1 | >= 100 mg/l (NOEL; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value) |

12.2. Persistence and degradability

| distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|--|
| Persistence and degradability | Not readily biodegradable in water. Adsorbs into the soil. |

12.3. Bioaccumulative potential

| distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|------------------------------------|
| Bioaccumulative potential | No bioaccumulation data available. |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No known effect on the ozone layer
Effect on global warming : No known ecological damage caused by this product.
No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not a dangerous good in sense of transport regulations

TDG

Refer to current TDG Canada for further Canadian regulations

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

| PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5 | |
|---|---|
| EPA TSCA Regulatory Flag | Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed |

| distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|--|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

PEAK High Mileage Passenger Car Motor Oil SAE 5W-20 SN/GF-5

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

WHMIS Classification

distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information

Full text of H-statements:

| | |
|---------------------------------|--|
| Acute Tox. 3 (Inhalation:vapor) | Acute toxicity (inhalation:vapor) Category 3 |
| Acute Tox. 4 (Inhalation:vapor) | Acute toxicity (inhalation:vapor) Category 4 |
| H331 | Toxic if inhaled |
| H332 | Harmful if inhaled |

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 °F (93 °C). (Class IIIB)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS GHS US (GHS HazCom 2012) OWI w/Supp OEL's

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.