



PEAK

COMMERCIAL & INDUSTRIAL

HEAVY-DUTY DIESEL MOTOR OIL

FOR USE IN CNG + LNG ENGINES

SAE 15W-40

DESCRIPTION:

PEAK® HD DIESEL 15W-40 MOTOR OIL FOR USE IN CNG & LNG ENGINES is a low ash heavy duty diesel engine oil designed for use in natural gas heavy duty diesel engines requiring Cummins CES20074 and Detroit Diesel PG05 93K16 quality levels. PEAK HD DIESEL 15W-40 MOTOR OIL FOR USE IN CNG & LNG ENGINES is formulated with premium high quality Group II base oils and state-of-the-art additives to produce a high quality finished product that provides superior engine protection and cleanliness. PEAK® HD DIESEL 15W-40 MOTOR OIL FOR USE IN CNG & LNG ENGINES provides a uniquely balanced premium formulation that minimizes ash deposits, oxidation, nitrification, valve regression, and engine wear.

BENEFITS:

- Excellent engine protection and cleanliness
- Strong oxidation and nitration resistance
- Excellent wear protection
- Improved sludge control

APPLICATION:

PEAK HD DIESEL 15W-40 MOTOR OIL FOR USE IN CNG & LNG ENGINES is recommended in mobile applications where compressed natural gas (CNG), liquid natural gas (LNG), or propane is used. It is recommended for bus, delivery, and service truck fleets.



SHIPPING INFORMATION:

	3/1 Gallon		55 Gallon Drum
Unit Weight (lbs.)	8.17	Unit Weight (lbs.)	450
Case/Pallet Weight*	23.25/1352	Pallet Weight*	1850
Units per Pallet	168	Units per Pallet	4
Cases per Pallet	56	Units per Truck	84
Units per Truck	3528	Cases/Pallets per Truck	21
Cases/Pallets per Truck	1176/21	Pallet Size (inches)	46 x 48 x 40.5
Case Size (inches)	13.81 x 8.19 x 12.38		
Cases per Row/Rows High	14/4		
Pallet Size (inches)	48X40X54.25		

*Includes pallet weight of 50 lbs.

PRODUCT INFORMATION:

15W-40 Natural Gas

Typical Properties

			Individual UPC Code	Case UPC Code	Case SCC-14 Code
Specific Gravity	.85	Bulk Part#	P4MA50	-	-
Viscosity @ 40°C, cSt	111	Drum Part#	P4MA51	0-74804-05591-7	-
Viscosity @ 100°C, cSt	15.5	1 Gallon Part#	P4MA53G	0-74804-05590-0	0-74804-15590-7
Viscosity Index	146				1-00-74804-05590-7
Pour Point, °C	-32				
Flash Point, °C	231				
Base Number	>4.5				
Sulfated Ash wt%	.5				



Distributed by Old World Industries, LLC Northbrook, IL 60062
 p 800.323.5440 www.peakauto.com
 ©2015 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.

RUN TRUE™