



PEAK GEAR OIL

DESCRIPTION:

PEAK® SAE 80W-90 GEAR OIL is a multi-purpose gear oil formulated to meet the latest requirements of manufacturers requiring API GL-5 lubricants. PEAK® SAE 80W-90 Gear Lubricant is a blend of high quality base stocks with extreme pressure additives that provide protection under severe operating conditions, including automotive applications.

PEAK® SAE 85W-140 GEAR OIL is a blend of high quality, high VI base stocks with sulfur-phosphorous extreme pressure additives that provide exceptional protection under severe operating conditions. PEAK® SAE 85W-140 GEAR OIL is a multi-purpose gear oil that exceeds the latest requirements of gear and transmission manufacturers requiring API GL-5 or API MT-1 level lubricants.

BENEFITS:

- Limited Slip
- Meets API GL-5 specification
- Meets MT-1 specification
- Meets Mack GO-J specification
- Meets MIL-L-2105D Military specification
- Outstanding anti-weld, anti-scuff and anti-wear properties
- Provides exceptional gear and bearing protection
- Helps prevent wear caused by lubrication foaming and aeration
- Protects against damaging rust and corrosion

APPLICATION:

PEAK® SAE 80W-90 and 85W-140 GEAR OILS are recommended for use in manual transmissions, limited slip, differentials, final drives and other gear cases in passenger cars, light duty trucks as well as axles of heavy duty trucks, off-road equipment, tractors and outboard motors. Viscosity recommendations vary according to temperature and engine manufacturer. Always consult your owner's manual for correct viscosity choice and service category recommendations.



SHIPPING INFORMATION:

	6/1 Quart	3/1 Gallon	5 Gallon Pail	16 Gallon Keg	55 Gallon Drum
Pack	2	8.2	40.6	140	450
Unit Weight (lbs.)	1,246	1,490	1,755.2	1,310	1,850
Pallet Weight*	528	180	42	9	4
Units per Pallet	88	60	-	-	-
Cases per Pallet/Truck	11,088	3,780	882	189	84
Units per Truck	21	21	21	21	21
Pallets per Truck	22/4	15/4	14/3	-	-
Cases per row/Rows high					

(* Including pallet weight of 50lbs.)

PRODUCT INFORMATION:

Test (Method)	80W-90	85W-140	80W-90	85W-140
API Gravity (ASTM D-287)	27.5	26	Quart Part Number	P9G0876
Viscosity			Gallon Part Number	P9G083
'@ 100 °C, cSt (ASTM D-445)	14	26.4	Pail Part Number	P9G085
Viscosity Index (ASTM D-2270)	100	100	Keg Part Number	P9G086
			Drum Part Number	P9G081
			Bulk Part Number	P9G080
	80W-90	85W-140	80W-90	85W-140
Quart UPC Code	0-74804-04296-2	0-74804-04298-6	Pail UPC Code	0-74804-03456-1
Quart Case UPC Code	0-74804-14296-9	0-74804-14298-3	Keg UPC Code	0-74804-03457-8
Quart SCC-14 Code	1-00-74804-04296-9	1-00-74804-04298-3	Drum UPC Code	0-74804-03455-4
Gallon UPC Code	0-74804-04297-9	0-74804-04299-3		
Gallon Case UPC Code	0-74804-14297-6	0-74804-14299-0		
Gallon SCC-14 Code	1-00-74804-04297-6	1-00-74804-04299-0		



Distributed by Old World Industries, LLC Northbrook, IL 60062

p 800.323.5440 www.peakauto.com

©2015 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.

RUN TRUE™