



PEAK

**50/50 PREDILUTED
ANTIFREEZE
+ COOLANT**
**GLOBAL
LIFETIME**



DESCRIPTION:

PEAK® Global LifeTime™ 50/50 Prediluted Antifreeze + Coolant features a patented, advanced organic acid technology that provides guaranteed lifetime protection - for as long as you own your vehicle!* Its patented inhibitors will provide maximum protection against damaging rust and corrosion in all automobiles and light-duty trucks worldwide, regardless of make, model, year or original antifreeze color.

BENEFITS:

- Provides guaranteed lifetime protection for as long as you own your vehicle when a complete cooling system flush and fill is performed and specified maintenance followed*
- Formulated for use in all American, Asian, and European automobiles
- Features a patented non 2-EH formula that is phosphate-free and silicate-free
- Can be used to top-off any color of automobile antifreeze including green, yellow, orange, fuschia, blue and red
- Amber color will not change the current antifreeze color when used for topping off
- Meets ASTM D-3306 + ASTM D-4340
- Prediluted Ready Use formula for topping off

SPECIFICATIONS:

- ANFOR R 15-601
- BS 6580 (British Standard)
- Chrysler MS7170
- Chrysler MS9769
- Ford ESE-M97B44-A
- Ford WSS-M97B51-A1
- FVV HEFT R443 (Germany)
- GM 6277M (DEX-COOL® Spec)
- JASO M325 (Japan)
- JIS K 2234 (Japan)
- SAE J1034
- Mercedes Benz DBL 7700

Properties

Specific Gravity 60/60°F
 Boiling Point, Reflux
 Foam Test**
 pH, 50% Volume Solution
 Flash Point, COC
 Total Water, Wt. %
 Total Glycols, Wt. %
 Color

Typical Values

1.070-1.080
 265°F Min.*
 50 ml./3 sec. Max.
 7.5-10.0
 250°F Min.
 50% Min.
 50% Max.
 Amber

ASTM Test Method

D-1122
 D-1120
 D-1881
 D-1287
 D-92
 D-1123
 D-202

**With a 15 psi pressure cap

Protection Chart (°F)

*Using a 15 psi pressure cap

Concentration	50%
Boiling Point*	265°F
Freezing Point	-34°F

*At sea level atmospheric pressure with 15lb. pressure cap. The boiling point decreases about 2°F per 1,000 feet of altitude and increases about 2.5°F per pound developed in the system.

Part Number	PXAB53	Cases Per Pallet	36
Gallon UPC	0-74804-00243-0	Pallets/Cases per Truck	20/720
Case UPC	0-74804-10243-7	Units per Truck	4,320
Case SCC-14	1-00-74804-00243-7	Truckload Weight***	42,040lbs.
Pack/Unit Case	6/1 Gallon (3.78 Liters)	Pallet Size	48"L x 40"W x 53 ^{3/4} "H
Weight/Cube	57 lbs./1.53 cu. ft.	Pallet Weight (inc. A/F & pallet)	2,102 lbs.
Case Dimensions	15.8"L X 12.6"W X 12.25"H	Cases/Rows High	9/4

(*) Includes Pallet Wt.: 20 @ 50 lbs. ea. = 1,000 lbs. Product Liability Information/Material Safety Data available upon request.



Distributed by Old World Industries, LLC Northbrook, IL 60062
 p 800.323.5440 www.peakauto.com
 ©2015 PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC.
 Long Life is a registered trademark of Warren Distribution, Inc.

RUN TRUE™