



Blue Mountain Professional Full Synthetic Motor Oils are formulated with high quality synthetic base stocks and are fortified with an advanced additive technology to provide maximum protection for today's modern engines. Blue Mountain Professional Full Synthetic Motor Oils meet most US and European industry standards like ILSAC GF-5 and API SN Service Classification.

Blue Mountain[™]
PROFESSIONAL



PROFESSIONAL AUTO CARE PRODUCTS



Blue Mountain™

PROFESSIONAL

Quart Part Number

	B2MS07-01	B2MS57-01	B3MS57-01	B3MS17-01
SAE Viscosity Grade	0W-20	5W-20	5W-30	10W-30
API Classification	SN	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5	GF-5

Test (Method)

	0W-20	5W-20	5W-30	10W-30
API Gravity (ASTM D-287) Viscosity	35.62	34.76	34.35	33.86
'@ 40°C, cSt (ASTM D-445)	42.71	47.26	57.86	62.97
'@ 100°C, cSt (ASTM D-445)	8.06	8.53	10.14	10.23
Viscosity Index (ASTM D-2270)	165	159	164	150
Sulfated Ash. % Mass	0.83	0.9	0.92	0.91
Pour Point	-51°C	-48°C	-45°C	-45°C
Flash Point	224°C	228°C	226°C	228°C
NOACK Volatility %	13.8	11.7	11.2	11.7

Quart UPC Code

Case UPC Code

Case SCC-14 Code

0W-20

0-74804-03363-2

0-74804-13363-9

1-00-74804-03363-9

5W-20

0-74804-03254-3

0-74804-13254-0

1-00-74804-03254-0

5W-30

0-74804-03255-0

0-74804-13255-7

1-00-74804-03255-7

10W-30

0-74804-03256-7

0-74804-13256-4

1-00-74804-03256-4

Product Shipping Info

Case Weight

Pallet Weight w/ Product*

Truckload Weight*

0W-20

24.12 lbs.

2,076 lbs.

43,452 lbs.

5W-20

24.12 lbs.

2,076 lbs.

43,452 lbs.

5W-30

24.39 lbs.

2,099 lbs.

43,938 lbs.

10W-30

24.35 lbs.

2,095 lbs.

43,848 lbs.

- Meets most warranty requirements for U.S., European and Japanese cars and light trucks with gasoline and gasoline turbo charged engines where API SN, SL, SJ or SH are specified
- Exceeds ILSAC GF-5 energy conserving performance standards
- Protection against high temperature deposits that can damage your engine
- Reduced friction and wear at engine start-up in cold weather
- Maximum protection against viscosity breakdown
- Protects engines under demanding stop and go driving conditions
- Meets the highest U.S. standards for automotive engine wear protection
- Protects against the formation of sludge and varnish deposits on engine parts

Pack/Units Per Case	12/1 Quart	Pallets/Cases Per Truck	21/1,764
Cubic Feet	.73 cu Ft.	Units Per Truck	21,168
Case Dimensions	13.25" L x 10.25" W x 9.25" H	Pallet Size	48" L x 40" W x 60.5" H
Cases Per Pallet	84	Cases/Rows High	14/6

HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your Blue Mountain Professional Products Supplier at www.bluemountainprofessional.com, or by calling Old World Industries technical support line at 1-800-477-5847.

Distributed by
Old World Industries, LLC
Northbrook, IL 60062-1851
1-800-323-5440
Made in U.S.A.
www.bluemountainprofessional.com
©2011



Blue Mountain™

PROFESSIONAL

Old World Industries, LLC

4065 Commercial Avenue Northbrook, IL 60062 • 1-800-323-5440 • www.bluemountainprofessional.com

Blue Mountain Professional and Blue Mountain Professional Graphic are trademarks of Old World Industries, LLC.

©2011 Old World Industries, LLC